





Knauf 'CW' Profile Studs

Galvanized lightweight steel sections to be used as vertical stud framing for Knauf partitions and wall linings. Our standard high quality metal section with detial labeling for easy identification on site. Knauf metal sections are cold-rolled from high grade galvanized steel sheets that complies with ASTM 645 - 09a Standard.



Knauf 'CW' Profile Studs ASTM



Product Description

Galvanized lightweight steel sections to be used as vertical stud framing for Knauf partitions and wall linings. Our standard high quality metal section with detial labeling for easy identification on site. Knauf metal sections are cold-rolled from high grade galvanized steel sheets that complies with ASTM 645 - 09a Standard.

Technical Data

CW Studs						
Dimensions (mm)						
Thickness	Web	Flange	Length	Meters Per Pack	Pieces Per Pack	Weight (Kg approx.)
0.5	41	33	3000	480	160	216
0.5	64	33	3000	480	160	216
0.5	89	33	3000	432	96	273
0.5	102	33	3000	384	144	261
0.5	152	33	3000	588	96	252
0.9	41	33	3000	480	160	384
0.9	64	33	3000	480	160	384
0.9	89	33	3000	288	96	323
0.9	102	33	3000	288	144	347
0.9	152	33	3000	204	64	317
	0.5 0.5 0.5 0.5 0.5 0.9 0.9 0.9 0.9 0.9	0.5 41 0.5 64 0.5 89 0.5 102 0.5 152 0.9 41 0.9 64 0.9 89 0.9 102	Thickness Web Flange 0.5 41 33 0.5 64 33 0.5 64 33 0.5 102 33 0.5 152 33 0.9 41 33 0.9 89 33 0.9 64 33 0.9 64 33 0.9 64 33 0.9 89 33 0.9 89 33 0.9 102 33	Thickness Web Flange Length 0.5 41 33 3000 0.5 64 33 3000 0.5 64 33 3000 0.5 64 33 3000 0.5 102 33 3000 0.5 152 33 3000 0.9 41 33 3000 0.9 64 33 3000 0.9 64 33 3000 0.9 89 33 3000 0.9 102 33 3000	Dimensions (mm) Thickness Web Flange Length Meters Per Pack 0.5 41 33 3000 480 0.5 64 33 3000 480 0.5 64 33 3000 480 0.5 102 33 3000 432 0.5 152 33 3000 588 0.9 41 33 3000 480 0.9 64 33 3000 480 0.9 64 33 3000 288 0.9 102 33 3000 288	Thickness Web Flange Length Meters Per Pack Pieces Per Pack 0.5 41 33 3000 480 160 0.5 64 33 3000 480 160 0.5 64 33 3000 480 160 0.5 89 33 3000 432 96 0.5 102 33 3000 588 96 0.5 152 33 3000 480 160 0.9 41 33 3000 480 160 0.9 64 33 3000 480 160 0.9 64 33 3000 288 96 0.9 89 33 3000 288 96 0.9 102 33 3000 288 144

available on request.

Notes:

Knauf profiles are produced in 3000mm length, custom lengths are available on request.

Other web sizes not mentioned in datasheet are also available, please contact Knauf LLC sales department for checking availability.

Knauf Head Office

- Phone: +971 4 337 7170
- Fax: +971 4 334 9659
- P.O. Box: 112871, Dubai

▶ info@knauf.ae

www.**kNAUF**.ae

Knauf Qatar Branch P.O.Box 27111 Doha, State of Qatar Tel: +974 44528191 Fax: +974 44528181

Knauf Manufacturing Plant P.O.Box 50006 Ras Al Khaimah, U.A.E. Tel: +971 7 221 5300 Fax: +971 7 221 5301



The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of this employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefullness of any failure in installation or constructing structure installation or building or caused by using this leaflet. Readers are adviced to independently verify this information prior to reply on it. In particular, readers must obtain appropriate independent advice on the use of products in specific structures, installations or buildings to ensure compliance with all regulations, in cluding health and safety regulations. Knauf reserves the right to amend technical specification without notice.

The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.