



AQUAPANEL®

06/2016

## AQUAPANEL® Tape (10 cm)

Glass fabric joint tape with alkali-resistant coating

Be certain,  
choose AQUAPANEL®

AQUAPANEL®



## Description

AQUAPANEL® Tape (10 cm) is a glass fibre tape with an alkali-resistant coating. It is used to reinforce joints on walls, ceilings and floors (only AQUAPANEL® Floor Tile Underlay) in interior areas and on walls and ceilings in exterior areas.

## Technical data

Weight/unit area	approx. 160 g/m <sup>2</sup>	approx. 160 g/m <sup>2</sup>
Mesh size	4 x 4 mm	4 x 4 mm
Initial tear strength	approx. 2200 N/5 cm	approx. 2200 N/5 cm
Thickness	approx. 0.5 mm	approx. 0.5 mm
Width	10 cm	10 cm
Length	20 m	50 m
Colour	blue	blue

## Processing/application

Fill joints with AQUAPANEL® Joint Filler & Skim Coating – white (interior walls and ceilings on AQUAPANEL® Cement Board Indoor), AQUAPANEL® Joint Filler – grey (exterior ceilings and walls on AQUAPANEL® Cement Board Outdoor), AQUAPANEL® SkyLite Joint Filler & Skim Coating (exterior and interior ceilings on AQUAPANEL® Cement Board SkyLite), or tile adhesive (interiors on AQUAPANEL® Cement Board Floor Tile Underlay) and embed AQUAPANEL® Tape (10 cm).

## Material coverage

Approx. 2.1 m/m<sup>2</sup>

## Method of delivery/storage

100 mm wide rolls x 20 m long, 18 rolls/carton.

Item code: 465546

100 mm wide rolls x 50 m long, 12 rolls/carton.

Item code: 429471

Store in a dry place and protect from moisture.

**AQUAPANEL®**

[www.AQUAPANEL.com](http://www.AQUAPANEL.com)

[aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany