





Knauf 'UW' Profile Tracks

Galvanized lightweight steel sections to be used as head and floor track members for Knauf Drywall Systems. Our standard high quality metal sections with detailed labeling allow for easy identification on site. Knauf metal sections are cold-rolled from high-grade galvanized steel sheets that complies with ASTM 645 - 9a Standard.



Knauf 'UW' Profile Tracks ASTM



Product Description

Galvanized lightweight steel sections to be used as head and floor track members for Knauf Drywall Systems. Our standard high quality metal sections with detailed labeling allow for easy identification on site. Knauf metal sections are cold-rolled from high-grade galvanized steel sheets that complies with ASTM 645 - 9a Standard.

Technical Data

UW Tracks

| Dimensions (mm) | | | | | | | | Dimensions (mm) | | | | | | | |
|-----------------|-----|--------|--------|--------------------|--------------------|---------------------|-------|-----------------|-----|--------|--------|--------------------|--------------------|---------------------|--|
| Thickness | Web | Flange | Length | Meters Per Pack | Pieces Per Pack | Weight (Kg approx.) | Thick | ness | Web | Flange | Length | Meters Per Pack | Pieces Per Pack | Weight (Kg approx.) | |
| 0.5 | 41 | 25 | 3000 | 600 | 200 | 215 | 0. | 5 | 41 | 60 | 3000 | 600 | 200 | 374 | |
| 0.5 | 64 | 25 | 3000 | 672 | 244 | 297 | 0. | 5 | 64 | 60 | 3000 | 384 | 128 | 274 | |
| 0.5 | 89 | 25 | 3000 | 288 | 96 | 155 | 0. | 5 | 89 | 60 | 3000 | 288 | 96 | 232 | |
| 0.5 | 102 | 25 | 3000 | 300 | 100 | 176 | 0. | 5 | 102 | 60 | 3000 | 180 | 60 | 155 | |
| 0.5 | 152 | 25 | 3000 | 192 | 64 | 150 | 0. | 5 | 152 | 60 | 3000 | 144 | 48 | 152 | |
| 0.9 | 41 | 25 | 3000 | 600 | 200 | 386 | 0. | 9 | 41 | 60 | 3000 | 600 | 200 | 670 | |
| 0.9 | 64 | 25 | 3000 | 384 | 128 | 306 | 0. | 9 | 64 | 60 | 3000 | 192 | 64 | 247 | |
| 0.9 | 89 | 25 | 3000 | 288 | 96 | 278 | 0. | 9 | 89 | 60 | 3000 | 144 | 48 | 210 | |
| 0.9 | 102 | 25 | 3000 | 300 | 100 | 315 | 0. | 9 | 102 | 60 | 3000 | 144 | 48 | 222 | |
| 0.9 | 152 | 25 | 3000 | 192 | 64 | 266 | 0. | 9 | 152 | 60 | 3000 | 144 | 48 | 273 | |

| Note | es: available on request. |
|------|---|
| | Knauf profiles are produced in 3000mm length, custom lengths are available on request. |
| | Other web sizes not mentioned in datasheet are also available, please contact Knauf LLC sales department for checking availability. |
| | |
| | |
| | |
| | |
| | |

Knauf Head Office

Phone: +971 4 337 7170

Fax: +971 4 334 9659

P.O. Box: 112871, Dubai

info@knauf.ae

Knauf Qatar Branch

P.O.Box 27111 Doha, State of Qatar Tel: +974 44528191

Fax: +974 44528181

Knauf Manufacturing Plant

P.O.Box 50006 Ras Al Khaimah, U.A.E. Tel: +971 7 221 5300 Fax: +971 7 221 5301



The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of this employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefullness of any failure in installation or constructing structure installation or building or caused by using this leaflet. Readers are adviced to independently verify this information prior to reply on it. In particular, readers must obtain appropriate independent advice on the use of products in specific structures, installations or buildings to ensure compliance with all regulations, in cluding health and safety regulations. Knauf reserves the right to amend technical specification without notice.



The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.